

































COLORING SOLUTIONS FOR ACRYLIC SEALANTS

In today's demanding market, the need for fast and flexible color production is a given. Holcolex A is a proven solution for acrylic sealants based on waterborne pigment pastes. Our solutions are designed to meet and exceed the coloring requirements from the factory to the end user. We work with the manufacturer to ensure a balance of cost and efficiency for batch production to cartridge filling. With outstanding color consistency and over 40 years of color formulation know-how, Holland Colours is able to tailor a solution to fit your individual needs.

- ✓ High pigment loading
- ✓ Excellent dispersion
- ✓ Low dosing
- ✓ Supports Automatic Dosing
- ✓ Standard colors and custom-specific colors

HOLCOLEX A BENEFITS AT A GLANCE

HOLCOLEX A

Full Shade	Tint 1:10 in Holcolex white LP 661809 A	Code	Specification of pigments used				
			Color Index	Pigment Loading (%)	Heat Resistance °C	Light Fastness	
						Full Shade	Tint
		LP 516209 A	PY 1	45	100	6-7	6
		LP 953309 A	PY 3	45	120	7-8	6-7
		LP 771809 A	PY 42	58	180	8	8
		LP 991809 A	PO 5	50	150	6-7	5
		LP 581809 A	PR 101	70	>300	8	8
		LP 401809 A	PR 101	66	>300	8	8
		LP 091809 A	PR 112	50	140	7-8	6
		LP 921809 A	PG 17	70	>300	8	7
		LP 731809 A	PG 7	52	300	8	8
		LP 151809 A	PB 15:3	44	250	8	8
		LP 351809 A	PB 15	48	180	8	7
		LP 061809 A	PV 23	30	280	8	7-8
		LP 391809 A	PBK 7	44	>300	8	8
		LP 611809 A	PBK 11	65	180	8	8
		LP 661809 A	PW 6	69	>300	8	8

FIND OUT MORE

Contact our sales people about purchasing quantities and deliveries or our technical experts for information about our technology and its implementation:

AMERICAS: richmond@hollandcolours.com | +1 765-935 0329 / toll-free: +1 800 723 0329

ASIA: surabaya@hollandcolours.com | +62 31 849 3939

EUROPE: info@hollandcolours.com | +31 (0)55 36 80 700

www.hollandcolours.com



DISCLAIMER

The information contained in this document has been prepared for presentation and promotional purposes and should only be used for guidance. This information should not be considered as a guarantee under any circumstances. Holland Colours makes no warranty, expressed or implied and gives no permission to practice any invention, patented or not, without a license and assumes no legal liability or responsibility for the accuracy, completeness or usefulness of any information contained herein and cannot accept liability for any injury, loss or damage resulting from reliance upon such information. All sales of Holland Colours products shall be subjected to the General conditions of Sale and Delivery of Holland Colours. If additional information is required, please contact your local Holland Colours' sales representative or visit our website: www.hollandcolours.com.

